

Twin Housing Lightweight, Portable Handcart Filter Pumps

Remove Water, Dirt, and Other Contaminants from Oils
MCP5E, Two-Stage Series-Flow Model
MDP5E, One-Stage Alternate-Flow Model

FEATURES

- 5 gpm Standard, 1 and 10 gpm Optional
- Economical two-cartridge configurations
- Choice of different cartridge combinations
- Quick and easy cartridge change
- Minimum oil spill during operation
- Self-contained, one person operation

DESCRIPTION

MCP5E Series-Flow – This model employs two different types of filter cartridges in series. Typically, the first of the MCP’s two housings is utilized as a prefilter. With heavy carbon or dirt contamination, this prefilter holds a cost-effective particulate or colloidal cartridge and the second in series holds an **Aquacon**® super-absorbent water removing cartridge. Since the **Aquacon** Cartridge seldom needs to be replaced, operating costs are reduced.

Other cartridge combinations have proven to be effective for filtering vacuum pump oil and other oils in corrosive environments. Use either an economical dirt cartridge or an **Aquacon** dirt and water cartridge in the first stage and either a Fuller’s Earth or an Activated Alumina cartridge in the second. The first stage removes dirt or dirt and water while the second removes acids, gums, surfactants, varnishes, soaps, color bodies, corrosive gasses, polar compounds, and oxidation products.

MDP5E Alternate-Flow – Only one housing on this model is utilized at a time. The operator can manually switch the oil flow from one housing to the other at his option. This is very useful when down-time is critical. The oil can filter through one side while the cartridge is being changed in the other housing with little or no interruption of oil flow.

Another application of the MDP5E is to use a different type of cartridge in each of the housings. An economical dirt removing cartridge, for example, can be employed in the first housing for routine filtering. When water is detected in the oil, the flow can be manually diverted to the second housing, containing an **Aquacon** Cartridge, for both water and dirt removal.



MDP5E-1

Contact your local Velcon Representative regarding other types of cartridges and cartridge combinations which are available.

APPLICATIONS

- | | |
|---------------------|----------------------|
| Hydraulic Oil | Heat Transfer Fluids |
| Gear Oil | Cutting Oil |
| Lube Oil | Mineral Oil |
| Transformer Oil | Phosphate Ester Oils |
| Vacuum Pump Oils: | Synthetic Oils |
| Hydrocarbon Base | |
| Perfluoropolyethers | |

SPECIFICATIONS

Standard Features, MCP5E and MDP5E

- 5 gpm standard flow rate
- Epoxy powder coated vessel, both interior and exterior
- Band Clamp vessel closure – no tools required
- Operating pressure to 100 psi
- 10" semi-pneumatic wheels
- Self-priming positive displacement pump with built-in pressure relief valve
- Static Pressure Gauge on each housing – to indicate when cartridge must be changed
- 1/2 hp, 115V, 1-phase, 60 Hz, 10 Amp TEFC Motor
- 10 ft. 3-wire power cord
- 9 ft. Inlet and Discharge Hose, 3/4" I.D.
- 3/4" NPT Male Fittings on hose ends
- Suction Y-Strainer mounted at pump inlet
- Weight: 157 lbs.
- Shipping Weight: 202 lbs.
- Height: 52", Width: 22", Depth: 22"

ORDERING INFORMATION

Specify model number as shown below.

Units are shipped without cartridges.

MCP5E-1 or MDP5E-1 115 v, 1-ph, 60 Hz

MCP5E-2 or MDP5E-2 230 v, 1-ph, 60 Hz

Also available: 1 gpm units, 10 gpm units,

3-phase power, 50 Hz power,

explosion proof motor, air motor

(contact Velcon)

OPTIONS & ACCESSORIES

550Y020 Flow Control Bypass

552Y030 Filter Bypass

703Z004 Differential Pressure Gauge (MCP)

703Y004 Differential Pressure Gauges (MDP)

722Y006 Digital Flowmeter

RECOMMENDED SPARES

Filter Cartridge, box of 6 ea (select from above)

G-1016 Std Buna-N Filter Housing Lid Gasket, 2 ea

G-1016A Viton-A Filter Housing Lid Gasket, 2 ea

FILTER CARTRIDGE SELECTION:

Application	Cartridge	Filter Area Sq. In.	Micrometer Rating, Specify:	Notes
Dirt Removal: Particulates Colloidals	FO-718PL Series Pleated Media	5000	1/3, 1/2, 1, 2, 5, 15 or 50	Maximum particulate filtration
	FO-618FGA Series Depth Media	N.A.	5, 10, or 25	Most cost effective for "slime" removal
Dirt and Water Removal	AC-718 Series	2500	1 or 5	Removes dirt and 1 to 2 quarts water
	Aquacon®	2900	1/2	For circuit breaker & high-carbon oils
Acid Removal	LA-71801B Fuller's Earth			Use 1 gpm Filter Pumps
	LB-71801 Activated Alumina			Use 1 gpm Filter Pumps



Velcon products are sold and serviced by a world-wide representative network. To order, contact Headquarters or your **LOCAL REPRESENTATIVE**:

COMPANY HEADQUARTERS:

Velcon Filters, Inc.

1210 Garden of the Gods Road

Colorado Springs, CO 80907-3410

Phone: 1.800.531.0180 / 1.719.531.5855

Fax: 719.531.5690

e-mail: vfsales@velcon.com

www.velcon.com

MANUFACTURING PLANTS LOCATED AT:

Colorado Springs, Colorado

Sylacauga, Alabama

OVERSEAS AFFILIATES:

Frankfurt/M., Germany & Singapore

**Liquid Filtration
and Separation
Specialists**